

SC 810

Recommended Application:

Highway

Optional Application:

Regional

Trailer Axle

Medium and Long Distances



CHARACTERISTICS

Tread with side wings and rounded shoulders to minimize the effect of side drag in maneuvering.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
7.5	200	7 7/8	9	11/32	2,18	4,83	1,47	6,75	14,88	9.00R20	P	3,085	10,121
7.5	200	7 7/8	9	11/32	2,18	4,83	1,47	7,05	15,54	10.00R20 11R22.5	M	3,212	10,538
7.5	200	7 7/8	9	11/32	2,18	4,83	1,47	7,20	15,87	11.00R20 11R24.5	E	3,289	10,791
8	210	8 2/8	9	11/32	2,30	5,08	1,61	7,15	15,76	9.00R20	P	3,103	10,180
8	210	8 2/8	9	11/32	2,30	5,08	1,61	7,40	16,31	10.00R20 11R22.5	M	3,211	10,535
8	210	8 2/8	9	11/32	2,30	5,08	1,61	7,60	16,76	12R22.5 11R24.5	E	3,292	10,801
8.5	215	8 5/8	9	11/32	2,40	5,30	1,61	7,50	16,53	275/80R22.5	P	3,123	10,246
8.5	215	8 5/8	9	11/32	2,40	5,30	1,61	7,70	16,98	295/80R22.5	M	3,205	10,515
8.5	215	8 5/8	9	11/32	2,40	5,30	1,61	7,90	17,42	12R22.5 315/80R22.5 11R24.5	E	3,288	10,787
8.5	220	8 5/8	9	11/32	2,44	5,39	1,64	7,65	16,87	275/80R22.5	P	3,134	10,282
8.5	220	8 5/8	9	11/32	2,44	5,39	1,64	7,80	17,20	295/80R22.5	M	3,190	10,466
8.5	220	8 5/8	9	11/32	2,44	5,39	1,64	8,10	17,86	12R22.5 315/80R22.5 11R24.5	E	3,302	10,833
9	230	9	9	11/32	2,57	5,67	1,73	7,95	17,53	275/80R22.5	P	3,088	10,131
9	230	9	9	11/32	2,57	5,67	1,73	8,25	18,19	295/80R22.5	M	3,206	10,518
9	230	9	9	11/32	2,57	5,67	1,73	8,45	18,63	12R22.5 315/80R22.5 11R24.5	E	3,294	10,807

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET