

SC 811

Recommended Application:

Highway

Optional Application:

Regional

Trailer Axle

Medium and Long Distances




CHARACTERISTICS

Tread with rounded shoulders to minimize the effect of lateral drag in maneuvers.

TECHNICAL DATA

| N# | Width | | Tread Depth | | Weight/m/Lbs./Foot | | | Weight/unit/Lbs. | | Recommended Tire | Size | Length | |
|------|-------|--------|-------------|-------|--------------------|-------|--------|------------------|-------|----------------------------------|------|--------|--------|
| | mm | In | mm | In | kg/m | Lbs/m | Lbs/ft | kg | Lbs | | | mm | ft |
| 8.5 | 220 | 8 5/8 | 12 | 15/32 | 2,94 | 6,48 | 1,97 | 9,22 | 20,33 | 275/80R22.5 | P | 3,140 | 10,301 |
| 8.5 | 220 | 8 5/8 | 12 | 15/32 | 2,94 | 6,48 | 1,98 | 9,50 | 20,94 | 295/80R22.5 11R22.5 | M | 3,230 | 10,596 |
| 8.5 | 220 | 8 5/8 | 12 | 15/32 | 2,94 | 6,48 | 1,97 | 9,68 | 21,34 | 11.00R20 11R24.5 | E | 3,300 | 10,826 |
| 9 | 230 | 9 | 12 | 15/32 | 3,07 | 6,77 | 2,06 | 9,63 | 21,23 | 275/80R22.5 | P | 3,140 | 10,301 |
| 9 | 230 | 9 | 12 | 15/32 | 3,07 | 6,77 | 2,07 | 9,93 | 21,89 | 295/80R22.5 11R22.5 | M | 3,230 | 10,596 |
| 9 | 230 | 9 | 12 | 15/32 | 3,07 | 6,77 | 2,06 | 10,12 | 22,31 | 12R22.5 11R24.5 | E | 3,300 | 10,826 |
| 9.5 | 240 | 9 4/8 | 12 | 15/32 | 3,21 | 7,08 | 2,29 | 10,70 | 23,59 | 275/80R22.5 | P | 3,140 | 10,301 |
| 9.5 | 240 | 9 4/8 | 12 | 15/32 | 3,21 | 7,08 | 2,16 | 10,38 | 22,88 | 295/80R22.5 | M | 3,230 | 10,596 |
| 9.5 | 240 | 9 4/8 | 12 | 15/32 | 3,21 | 7,08 | 2,15 | 10,58 | 23,32 | 12R22.5 315/80R22.5 11R24.5 | E | 3,300 | 10,826 |
| 10 | 250 | 9 7/8 | 12 | 15/32 | 3,34 | 7,36 | 2,25 | 10,80 | 23,81 | 295/80R22.5 | M | 3,230 | 10,596 |
| 10 | 250 | 9 7/8 | 12 | 15/32 | 3,34 | 7,36 | 2,24 | 11,01 | 24,27 | 315/80R22.5 | E | 3,300 | 10,826 |
| 10.5 | 260 | 10 2/8 | 12 | 15/32 | 3,47 | 7,65 | 2,33 | 11,22 | 24,74 | 295/80R22.5 | M | 3,230 | 10,596 |

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET