

SC 822

Piso Pavimentado
Eje Libre
Media y Larga Distancia



CARACTERÍSTICAS

Banda con hombros robustos y ranuras en "V" diseñadas para maximizar el rendimiento.

DATOS TÉCNICOS

N#	Ancho		Profundidad		Peso/m/Lbs./Pies			Peso/unit/Lbs.		Neumático recomendado	Tamaño	Largo	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8.5	220	8 5/8	13	16/32	3,23	7,12	2,17	9,97	21,98	275/80R22.5	P	3.090	10,138
8.5	220	8 5/8	13	16/32	3,22	7,10	2,16	10,30	22,71	295/80R22.5 11R22.5	M	3.200	10,499
8.5	220	8 5/8	13	16/32	3,22	7,10	2,16	10,65	23,48	11.00R20 11R24.5	E	3.310	10,860
9	230	9	13	16/32	3,26	7,19	2,19	10,07	22,20	275/80R22.5	P	3.090	10,138
9	230	9	13	16/32	3,26	7,19	2,19	10,43	22,99	295/80R22.5 11R22.5	M	3.200	10,499
9	230	9	13	16/32	3,26	7,19	2,19	10,82	23,85	12R22.5 11R24.5	E	3.320	10,892
9.5	240	9 4/8	13	16/32	3,40	7,50	2,29	10,89	24,01	295/80R22.5	M	3.200	10,499
9.5	240	9 4/8	13	16/32	3,40	7,50	2,28	11,28	24,87	12R22.5 315/80R22.5 11R24.5	E	3.320	10,892
10	250	9 7/8	13	16/32	3,54	7,80	2,38	11,27	24,85	295/80R22.5	M	3.180	10,433
10	250	9 7/8	13	16/32	3,54	7,80	2,38	11,76	25,93	315/80R22.5	E	3.320	10,892
10.5	260	10 2/8	13	16/32	3,92	8,64	2,64	12,95	28,55	315/80R22.5	E	3.300	10,827
11	270	9 7/8	13	16/32	4,05	8,93	2,71	13,37	29,48	315/80R22.5	E	3.310	10,860

BANDAS PRECURADAS - SILVERCAP



WWW.SILVERCAP.NET