

# SC 822

Recommended Application:

Highway

Optional Application:

Regional

Trailer Axle

Medium and Long Distances



## CHARACTERISTICS

Tread with strength rib of shoulder-improve shoulders and “V” grooves designed to maximize performance.

## TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8.5	220	8 5/8	13	16/32	3,23	7,12	2,17	9,97	21,98	275/80R22.5	P	3,090	10,138
8.5	220	8 5/8	13	16/32	3,22	7,10	2,16	10,30	22,71	295/80R22.5   11R22.5	M	3,200	10,499
8.5	220	8 5/8	13	16/32	3,22	7,10	2,16	10,65	23,48	11.00R20   11R24.5	E	3,310	10,860
9	230	9	13	16/32	3,26	7,19	2,19	10,07	22,20	275/80R22.5	P	3,090	10,138
9	230	9	13	16/32	3,26	7,19	2,19	10,43	22,99	295/80R22.5   11R22.5	M	3,200	10,499
9	230	9	13	16/32	3,26	7,19	2,19	10,82	23,85	12R22.5   11R24.5	E	3,320	10,892
9.5	240	9 4/8	13	16/32	3,40	7,50	2,29	10,89	24,01	295/80R22.5	M	3,200	10,499
9.5	240	9 4/8	13	16/32	3,40	7,50	2,28	11,28	24,87	12R22.5   315/80R22.5 11R24.5	E	3,320	10,892
10	250	9 7/8	13	16/32	3,54	7,80	2,38	11,27	24,85	295/80R22.5	M	3,180	10,433
10	250	9 7/8	13	16/32	3,54	7,80	2,38	11,76	25,93	315/80R22.5	E	3,320	10,892
10.5	260	10 2/8	13	16/32	3,92	8,64	2,64	12,95	28,55	315/80R22.5	E	3,300	10,827
11	270	9 7/8	13	16/32	4,05	8,93	2,71	13,37	29,48	315/80R22.5	E	3,310	10,860

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET