

SC 833

Piso Pavimentado
Eje Motriz
Corta y Media Distancia



CARACTERÍSTICAS

Banda de alto rendimiento que proporciona una excelente conducción y confort.

DATOS TÉCNICOS

N#	Ancho		Profundidad		Peso/m/Lbs./Pies			Peso/unit/Lbs.		Neumático recomendado	Tamaño	Largo	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
9	230	9	16	20/32	4,10	9,04	2,75	12,86	28,35	275/80R22.5	P	3.140	10,301
9	230	9	16	20/32	4,15	9,15	2,79	13,74	30,29	12R22.5 11R24.5	E	3.310	10,859
9.5	240	9 4/8	16	20/32	4,27	9,41	2,87	13,45	29,65	275/80R22.5	P	3.150	10,334
9.5	240	9 4/8	16	20/32	4,34	9,57	2,91	14,40	31,75	12R22.5 315/80R22.5 11R24.5	E	3.320	10,892
10	250	9 7/8	16	20/32	4,57	10,08	3,06	14,55	32,08	295/80R22.5	M	3.190	10,466
10.5	260	10 2/8	16	20/32	4,75	10,47	3,20	15,22	33,35	295/80R22.5	M	3.200	10,499
9	230	9	18	23/32	4,56	10,05	3,07	14,05	30,97	275/80R22.5	P	3.080	10,104
9.5	240	9 4/8	18	23/32	4,76	10,49	3,20	14,66	32,32	275/80R22.5	P	3.080	10,104
9.5	240	9 4/8	18	23/32	4,76	10,49	3,20	15,20	33,51	295/80R22.5	M	3.190	10,465
10	250	9 7/8	18	23/32	4,95	10,91	3,33	15,24	33,60	275/80R22.5	P	3.080	10,104
10	250	9 7/8	18	23/32	5,95	13,12	3,33	15,84	34,92	295/80R22.5	M	3.200	10,498

BANDAS PRECURADAS - SILVERCAP



WWW.SILVERCAP.NET