

SC 834

Piso Pavimentado
Eje Motriz
Corta y Media Distancia



CARACTERÍSTICAS

Banda de alto rendimiento con bloques robustos y gran relación peso/metro.

DATOS TÉCNICOS

N#	Ancho		Profundidad		Peso/m/Lbs./Pies			Peso/unit/Lbs.		Neumático recomendado	Tamaño	Largo	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	210	8 2/8	15	19/32	4	8,82	2,69	12,47	27,49	275/80R22.5	P	3.120	10,236
8	210	8 2/8	15	19/32	4	8,82	2,69	13,02	28,70	295/80R22.5 11R24.5	M	3.250	10,663
8	210	8 2/8	15	19/32	4	8,82	2,69	13,26	29,23	12R22.5 11R24.5	E	3.320	10,892
8,5	220	8 5/8	15	19/32	4,07	8,97	2,73	12,63	27,84	275/80R22.5	P	3.110	10,203
8,5	220	8 5/8	15	19/32	4,07	8,97	2,73	13,20	29,10	295/80R22.5 11R24.5	M	3.240	10,630
8,5	220	8 5/8	15	19/32	4,07	8,97	2,73	13,49	39,74	11.00R20 11R24.5	E	3.310	10,860
9	230	9	15	19/32	4,12	9,08	2,77	12,78	28,18	275/80R22.5	P	3.100	10,171
9	230	9	15	19/32	4,12	9,08	2,77	13,37	29,48	295/80R22.5 11R24.5	M	3.240	10,630
9	230	9	15	19/32	4,12	9,11	2,77	13,71	30,23	12R22.5 11R24.5	E	3.320	10,892
9,5	240	9 4/8	15	19/32	4,40	9,70	2,96	13,66	30,12	275/80R22.5	P	3.110	10,203
9,5	240	9 4/8	15	19/32	4,40	9,70	2,96	14,25	31,42	295/80R22.5	M	3.240	10,630
9,5	240	9 4/8	15	19/32	4,40	9,70	2,96	14,63	32,25	12R22.5 315/80R22.5 11R24.5	E	3.320	10,892
10	250	9 7/8	15	19/32	4,58	10,10	3,08	14,74	32,50	295/80R22.5	M	3.320	10,564
10	250	9 7/8	15	19/32	4,58	10,10	3,08	15,14	33,38	315/80R22.5	E	3.300	10,827
10,5	260	10 2/8	15	19/32	4,82	10,63	3,24	15,55	34,28	295/80R22.5	M	3.230	10,597
10,5	260	10 2/8	15	19/32	4,82	10,63	3,24	15,98	35,23	315/80R22.5	E	3.300	10,827
9,5	240	9 4/8	18	23/23	5,15	11,35	3,46	16,02	35,32	275/80R22.5	P	3.110	10,203
9,5	240	9 4/8	18	23/23	5,15	11,35	3,46	16,69	36,80	295/80R22.5	M	3.240	10,630

BANDAS PRECURADAS - SILVERCAP



WWW.SILVERCAP.NET

SC 834

Piso Pavimentado
Eje Motriz
Corta y Media Distancia



CARACTERÍSTICAS

Banda de alto rendimiento con bloques robustos y gran relación peso/metro.

DATOS TÉCNICOS

N#	Ancho		Profundidad		Peso/m/Lbs./Pies			Peso/unit/Lbs.		Neumático recomendado	Tamaño	Largo	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
9.5	240	9 4/8	18	23/32	5,17	11,40	3,47	17,16	37,83	12R22.5 315/80R22.5 11R24.5	E	3.320	10,892
10	250	9 7/8	18	23/32	5,37	11,84	3,60	17,37	38,29	295/80R22.5	M	3.240	10,630
10	250	9 7/8	18	23/32	5,37	11,88	3,60	17,88	39,42	315/80R22.5	E	3.320	10,892
10.5	260	10 2/8	18	23/32	5,65	12,46	3,80	18,28	40,30	295/80R22.5	M	3.240	10,630
10.5	260	10 2/8	18	23/32	5,65	12,50	3,80	18,84	41,54	315/80R22.5	E	3.320	10,892

BANDAS PRECURADAS - SILVERCAP



WWW.SILVERCAP.NET