

SC 834

Piso Pavimentado
Eje Motriz
Corta y Media Distancia



CARACTERÍSTICAS

Banda de alto rendimiento con bloques robustos y gran relación peso/metro.

DATOS TÉCNICOS

N#	Ancho		Profundidad		Neumático Recomendado	Tamaño	Longitud (mm)
	mm	In	mm	In			
9	230	9	15	19/32	275/80R22.5	P	3.100
9	230	9	15	19/32	295/80R22.5 11R22.5	M	3.240
9.5	240	9 4/8	15	19/32	275/80R22.5	P	3.110
9.5	240	9 4/8	15	19/32	295/80R22.5	M	3.240
10	250	9 7/8	15	19/32	295/80R22.5	M	3.220
10.5	260	10 2/8	15	19/32	295/80R22.5	M	3.230
9.5	240	9 4/8	18	23/32	275/80R22.5	P	3.110
9.5	240	9 4/8	18	23/32	295/80R22.5	M	3.240
10	250	9 7/8	18	23/32	295/80R22.5	M	3.240
10.5	260	10 2/8	18	23/32	295/80R22.5	M	3.240

*Consultar la disponibilidad de productos con medidas especiales

BANDAS PRECURADAS - SILVERCAP

SILVERCAP.NET

