

SC 850

Todos os Pisos
Eixo Tração e Livre
Curta e Média Distância



CARACTERÍSTICAS

Banda tradicional para uso misto, sulcos em “V” evitam retenção de pedras.

DADOS TÉCNICOS

N#	Largura		Profundidade		Pneu Recomendado	Tamanho	Comprimento (mm)
	mm	In	mm	In			
6.5	180	7 1/8	14	18/32	215/75R17.5	MICRO	2.340
6.5	180	7 1/8	14	18/32	9.00R20	P	3.150
7	190	7 4/8	14	18/32	215/75R17.5	MICRO	2.390
7	190	7 4/8	14	18/32	9.00R20	P	3.120
7.5	200	7 7/8	15	19/32	10.00R20	M	3.200
8	210	8 2/8	15	19/32	9.00R20	P	3.090
8	210	8 2/8	15	19/32	10.00R20	M	3.220
8.5	220	8 5/8	15	19/32	275/80R22.5	P	3.130
8.5	220	8 5/8	15	19/32	295/80R22.5 11R22.5	M	3.230
9	230	9	15	19/32	275/80R22.5	P	3.130
9	230	9	15	19/32	295/80R22.5 11R22.5	M	3.230
9.5	240	9 4/8	15	19/32	275/80R22.5	P	3.130
9.5	240	9 4/8	15	19/32	295/80R22.5	M	3.210
10	250	9 7/8	15	19/32	295/80R22.5	P	3.120
10	250	9 7/8	15	19/32	295/80R22.5	M	3.200
10.5	260	10 2/8	15	19/32	295/80R22.5	M	3.210

*Consulte disponibilidade de produtos com tamanho especial

BANDAS PRÉ-MOLDADAS - SILVERCAP

SILVERCAP.NET

