

SC 850

Recommended Application:
Mixed / Regional

Optional Application:
Off the Road

Drive and Trailer Axles
Short and Medium Distances




CHARACTERISTICS

Traditional tread for on/off the road use. "V" grooves avoid stone retention.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
6.5	180	7 1/8	14	18/32	2,82	6,22	1,89	6,58	14,51	215/75R17.5	MICRO	2,340	7,677
6.5	180	7 1/8	14	18/32	2,82	6,22	1,90	8,89	19,60	9.00R20	P	3,150	10,334
7	190	7 4/8	14	18/32	2,96	6,53	2,60	9,24	20,37	215/75R17.5	MICRO	2,390	7,841
7	190	7 4/8	14	18/32	2,96	6,53	1,52	7,07	15,59	9.00R20	P	3,120	10,236

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET

SC 850

Recommended Application:
Mix Application

Optional Application:
Off the Road

Drive and Trailer Axles
Short and Medium Distances




CHARACTERISTICS

Traditional tread for on/off the road use. "V" grooves avoid stone retention.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
7.5	200	7 7/8	15	19/32	3,40	7,50	2,28	10,86	23,94	10.00R20	M	3,200	10,498
8	210	8 2/8	15	19/32	3,52	7,76	2,37	10,88	23,99	9.00R20	P	3,090	10,137
8	210	8 2/8	15	19/32	3,53	7,78	2,37	11,36	25,04	10.00R20	M	3,220	10,564
8.5	220	8 5/8	15	19/32	3,63	8,00	2,44	11,36	25,04	275/80R22.5	P	3,130	10,268
8.5	220	8 5/8	15	19/32	3,63	8,00	2,44	11,72	25,84	295/80R22.5 11R22.5	M	3,230	10,596
9	230	9	15	19/32	3,73	8,22	2,51	11,67	25,73	275/80R22.5	P	3,130	10,268
9	230	9	15	19/32	3,73	8,22	2,51	12,06	26,59	295/80R22.5 11R22.5	M	3,230	10,596
9	230	9	15	19/32	3,73	8,22	2,51	12,35	27,23	12R22.5 11R24.5	E	3,310	10,859
9.5	240	9 4/8	15	19/32	3,98	8,77	2,67	12,45	27,45	275/80R22.5	P	3,130	10,268
9.5	240	9 4/8	15	19/32	3,98	8,77	2,67	12,77	28,15	295/80R22.5	M	3,210	10,531
9.5	240	9 4/8	15	19/32	3,97	8,75	2,67	13,07	28,81	12R22.5 315/80R22.5 11R24.5	E	3,290	10,793
10	250	9 7/8	15	19/32	4,07	8,97	2,74	12,71	28,02	275/80R22.5	P	3,120	10,236
10	250	9 7/8	15	19/32	4,08	8,99	2,74	13,04	28,75	295/80R22.5	M	3,200	10,498
10	250	9 7/8	15	19/32	4,07	8,97	2,73	13,38	29,50	315/80R22.5	E	3,290	10,793
10.5	260	10 2/8	15	19/32	4,23	9,33	2,84	13,57	29,92	295/80R22.5	M	3,210	10,531
10.5	260	10 2/8	15	19/32	4,23	9,33	2,84	13,92	30,69	315/80R22.5	E	3,290	10,793

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET