

# SC 851

Recommended Application:  
Mix Application

Optional Application:  
Off the Road

Drive and Trailer Axles  
Short and Medium Distances



## CHARACTERISTICS

Traditional tread with less weight for on/off the road use. "V" grooves avoid stone retention.

## TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	210	8 2/8	13.5	17/32	3,16	6,97	2,12	9,88	21,78	9.00R20	P	3.130	10,269
8	210	8 2/8	13.5	17/32	3,16	6,97	2,12	10,08	22,22	10.00R20	M	3.190	10,466
8	210	8 2/8	13.5	17/32	3,16	6,97	2,12	10,50	26,15	12R22.5   11R24.5	E	3.320	10,892
8.5	220	8 5/8	13.5	17/32	3,33	7,30	2,22	10,43	22,99	275/80R22.5	P	3.150	10,335
8.5	220	8 5/8	13.5	17/32	3,29	7,30	2,22	10,67	23,52	295/80R22.5   11R22.5	M	3.220	10,564
9	230	9	13.5	17/32	3,46	7,63	2,32	10,82	23,85	275/80R22.5	P	3.130	10,268
9	230	9	13.5	17/32	3,43	7,63	2,32	11,07	24,41	295/80R22.5   11R22.5	M	3.200	10,499
9.5	240	9 4/8	13.5	17/32	3,58	7,98	2,43	11,22	24,74	275/80R22.5	P	3.100	10,171
9.5	240	9 4/8	13.5	17/32	3,65	7,98	2,43	11,72	25,84	295/80R22.5	M	3.240	10,631
10	250	9 7/8	13.5	17/32	3,77	8,32	2,53	12,07	26,61	295/80R22.5	M	3.210	10,531

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET