

SC 852

Todos los Pisos
Eje Motriz y Libre
Corta y Media Distancia



CARACTERÍSTICAS

Banda de alto rendimiento, con bloques robustos y ranuras con expulsores de piedras para proteger el casco.

DATOS TÉCNICOS

| N# | Ancho | | Profundidad | | Neumático Recomendado | Tamaño | Longitud (mm) |
|------|-------|--------|-------------|-------|-----------------------|--------|---------------|
| | mm | In | mm | In | | | |
| 7.5 | 210 | 8 2/8 | 18 | 23/32 | 9.00R20 | P | 3.150 |
| 7.5 | 210 | 8 2/8 | 18 | 23/32 | 10.00R20 | M | 3.210 |
| 8.5 | 220 | 8 5/8 | 18 | 23/32 | 275/80R22.5 | P | 3.130 |
| 8.5 | 220 | 8 5/8 | 18 | 23/32 | 295/80R22.5 11R22.5 | M | 3.200 |
| 9 | 230 | 9 | 18 | 23/32 | 275/80R22.5 | P | 3.150 |
| 9 | 230 | 9 | 18 | 23/32 | 295/80R22.5 11R22.5 | M | 3.220 |
| 9.5 | 240 | 9 4/8 | 18 | 23/32 | 275/80R22.5 | P | 3.140 |
| 9.5 | 240 | 9 4/8 | 18 | 23/32 | 295/80R22.5 | M | 3.200 |
| 10 | 250 | 9 7/8 | 18 | 23/32 | 295/80R22.5 | P | 3.150 |
| 10 | 250 | 9 7/8 | 18 | 23/32 | 295/80R22.5 | M | 3.220 |
| 10.5 | 260 | 10 2/8 | 18 | 23/32 | 295/80R22.5 | M | 3.220 |

*Consultar la disponibilidad de productos con medidas especiales

BANDAS PRECURADAS - SILVERCAP

SILVERCAP.NET

