

SC 852

Recommended Application:
Mix Application

Optional Application:
Off the Road

Drive and Trailer Axles
Short and Medium Distances



CHARACTERISTICS

High performance tread, with strenght blocks and grooves with stone expellers to protect the carcass.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Lenght	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	210	8 2/8	18	23/32	4,04	8,91	2,71	12,72	28,04	9.00R20	P	3.150	10,335
8	210	8 2/8	18	23/32	4,04	8,91	2,71	12,96	28,57	10.00R20	M	3.210	10,531
8	210	8 2/8	18	23/32	4,04	8,91	2,71	13,45	29,65	12R22.5 11R24.5	E	3.330	10,925
8.5	220	8 5/8	18	23/32	4,23	9,33	2,84	13,24	29,19	275/80R22.5	P	3.130	10,269
8.5	220	8 5/8	18	23/32	4,23	9,33	2,84	13,52	29,81	295/80R22.5 11R22.5	M	3.200	10,499
8.5	220	8 5/8	18	23/32	4,23	9,33	2,84	14,05	30,97	11.00R20 12R22.5 11R24.5	E	3.320	10,892
9	230	9	18	23/32	4,43	9,77	2,97	13,94	30,73	275/80R22.5	P	3.150	10,335
9	230	9	18	23/32	4,43	9,77	2,97	14,25	31,42	295/80R22.5 11R22.5	M	3.220	10,564
9	230	9	18	23/32	4,43	9,77	2,97	14,55	32,08	12R22.5 11R24.5	E	3.290	10,794
9.5	240	9 4/8	18	23/32	4,62	10,19	3,10	14,50	31,97	275/80R22.5	P	3.140	10,302
9.5	240	9 4/8	18	23/32	4,62	10,19	3,11	14,80	32,63	295/80R22.5	M	3.200	10,499
9.5	240	9 4/8	18	23/32	4,62	10,19	3,11	15,12	33,33	12R22.5 315/80R22.5 11R24.5	E	3.270	10,728
10	250	9 7/8	18	23/32	4,81	10,60	3,23	15,15	33,40	275/80R22.5	P	3.150	10,335
10	250	9 7/8	18	23/32	4,81	10,60	3,24	15,52	34,22	295/80R22.5	M	3.220	10,564
10	250	9 7/8	18	23/32	4,81	10,60	3,23	15,88	35,01	315/80R22.5	E	3.300	10,827
10.5	260	10 2/8	18	23/32	4,81	10,60	3,37	16,13	35,56	295/80R22.5	M	3.220	10,564

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET