

SC 860

Recommended Application:

Highway

Optional Application:

Regional

Drive Axle

Medium and Long Distances



CHARACTERISTICS

Tread with excellent traction power, open shoulders for better water drainage.

TECHNICAL DATA

| N# | Width | | Tread Depth | | Weight/m/Lbs./Foot | | | Weight/unit/Lbs. | | Recommended Tire | Size | Length | |
|------|-------|--------|-------------|-------|--------------------|-------|--------|------------------|-------|----------------------------------|------|--------|--------|
| | mm | In | mm | In | kg/m | Lbs/m | Lbs/ft | kg | Lbs | | | mm | ft |
| 8.5 | 220 | 8 5/8 | 20 | 25/32 | 4,15 | 9,15 | 2,79 | 12,81 | 28,24 | 275/80R22.5 | P | 3,090 | 10,137 |
| 8.5 | 220 | 8 5/8 | 20 | 25/32 | 4,15 | 9,15 | 2,79 | 13,23 | 29,17 | 295/80R22.5 11R22.5 | M | 3,190 | 10,465 |
| 9 | 230 | 9 | 20 | 25/32 | 4,59 | 10,12 | 3,07 | 14,60 | 32,19 | 295/80R22.5 11R22.5 | M | 3,180 | 10,492 |
| 9 | 230 | 9 | 20 | 25/32 | 4,59 | 10,12 | 3,08 | 15,09 | 33,27 | 12R22.5 11R24.5 | E | 3,290 | 10,793 |
| 9.5 | 240 | 9 4/8 | 20 | 25/32 | 4,79 | 10,56 | 3,24 | 15,34 | 33,82 | 295/80R22.5 | M | 3,180 | 10,432 |
| 9.5 | 240 | 9 4/8 | 20 | 25/32 | 4,79 | 10,56 | 3,22 | 15,78 | 34,79 | 12R22.5 315/80R22.5 11R24.5 | E | 3,290 | 10,793 |
| 10 | 250 | 9 7/8 | 20 | 25/32 | 4,99 | 11,00 | 3,35 | 15,85 | 34,94 | 295/80R22.5 | M | 3,180 | 10,432 |
| 10 | 250 | 9 7/8 | 20 | 25/32 | 4,99 | 11,00 | 3,36 | 16,43 | 36,22 | 315/80R22.5 | E | 3,290 | 10,793 |
| 10.5 | 260 | 10 2/8 | 20 | 25/32 | 5,19 | 11,44 | 3,48 | 16,49 | 36,35 | 295/80R22.5 | M | 3,180 | 10,432 |
| 10.5 | 260 | 10 2/8 | 20 | 25/32 | 5,19 | 11,44 | 3,49 | 17,12 | 37,74 | 315/80R22.5 | E | 3,300 | 10,826 |
| 11 | 270 | 10 5/8 | 20 | 25/32 | 5,39 | 11,88 | 3,62 | 17,15 | 37,81 | 295/80R22.5 | M | 3,180 | 10,432 |
| 11 | 270 | 10 5/8 | 20 | 25/32 | 5,39 | 11,88 | 3,62 | 17,82 | 39,29 | 315/80R22.5 | E | 3,310 | 10,859 |

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET