

# SC 864

Piso Pavimentado  
Eje Motriz  
Media y Larga Distancia



## CARACTERÍSTICAS

Banda tradicional con bloques robustos, excelente respuesta tractiva y gran drenaje del agua.

## DATOS TÉCNICOS

N#	Ancho		Profundidad		Neumático Recomendado	Tamaño	Longitud (mm)
	mm	In	mm	In			
8	205	8 2/8	17	22/32	9.00R20	P	3.140
8	205	8 2/8	17	22/32	10.00R20	M	3.220
8	210	8 2/8	17	22/32	9.00R20	P	3.140
8	210	8 2/8	17	22/32	10.00R20	M	3.220
8.5	215	8 5/8	17	22/32	275/80R22.5	P	3.120
8.5	215	8 5/8	17	22/32	10.00R20	M	3.200
8,5	220	8 5/8	17	22/32	275/80R22.5	P	3.090
8,5	220	8 5/8	17	22/32	295/80R22.5	M	3.200
9	230	9	17	22/32	275/80R22.5	P	3.090
9	230	9	17	22/32	295/80R22.5   11R22.5	M	3.200
9.5	240	9 4/8	17	22/32	275/80R22.5	P	3.090
9.5	240	9 4/8	17	22/32	295/80R22.5	M	3.200
10	250	9 7/8	17	22/32	295/80R22.5	M	3.200
10.5	260	10 2/8	17	22/32	295/80R22.5	M	3.200

\*Consultar la disponibilidad de productos con medidas especiales

BANDAS PRECURADAS - SILVERCAP



SILVERCAP.NET