

# SC 864

Recommended Application:

Highway

Optional Application:

Regional

Drive Axle

Medium and Long Distances



## CHARACTERISTICS

Traditional tread with straight blocks, excellent tractive response and great water drainage.

## TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	205	8 2/8	17	22/32	3,53	7,78	2,37	11,06	24,38	9.00R20	P	3,140	10,302
8	205	8 2/8	17	22/32	3,53	7,78	2,37	11,34	25,00	10.00R20	M	3,220	10,564
8	205	8 2/8	17	22/32	3,53	7,78	2,37	11,61	25,60	10.00R20	E	3,290	10,794
8	210	8 2/8	17	22/32	3,62	7,98	2,43	11,34	25,00	9.00R20	P	3,140	10,302
8	210	8 2/8	17	22/32	3,62	7,98	2,43	11,63	25,64	10.00R20	M	3,220	10,564
8	210	8 2/8	17	22/32	3,62	7,98	2,43	11,91	26,26	12R22.5   11R24.5	E	3,290	10,794
8.5	215	8 5/8	17	22/32	3,67	8,09	2,47	11,47	25,29	275/80R22.5	P	3,120	10,236
8.5	215	8 5/8	17	22/32	3,67	8,09	2,47	11,77	25,95	10.00R20	M	3,200	10,499
8.5	215	8 5/8	17	22/32	3,67	8,09	2,47	12,08	26,63	12R22.5   11R24.5	E	3,290	10,794
8.5	220	8 5/8	17	22/32	3,79	8,36	2,55	11,71	25,82	275/80R22.5	P	3,090	10,138
8.5	220	8 5/8	17	22/32	3,79	8,36	2,55	12,12	26,72	295/80R22.5	M	3,200	10,499
8.5	220	8 5/8	17	22/32	3,79	8,36	2,55	12,34	27,21	11.00R20   11R24.5	E	3,260	10,696
9	230	9	17	22/32	3,97	8,75	2,67	12,26	27,03	275/80R22.5	P	3,090	10,137
9	230	9	17	22/32	3,97	8,75	2,66	12,69	27,98	295/80R22.5   11R22.5	M	3,200	10,498
9	230	9	17	22/32	3,97	8,75	2,66	12,92	28,48	12R22.5   11R24.5	E	3,260	10,695
9.5	240	9 4/8	17	22/32	4,13	9,11	2,78	12,77	28,15	275/80R22.5	P	3,090	10,137
9.5	240	9 4/8	17	22/32	4,14	9,13	2,78	13,24	29,19	295/80R22.5	M	3,200	10,498
9.5	240	9 4/8	17	22/32	4,14	9,13	2,78	13,49	29,74	12R22.5   315/80R22.5   11R24.5	E	3,260	10,695
10	250	9 7/8	17	22/32	4,31	9,50	2,90	13,79	30,40	295/80R22.5	M	3,200	10,498

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET

# SC 864

Recommended Application:

Highway

Optional Application:

Regional

Drive Axle

Medium and Long Distances



## CHARACTERISTICS

Traditional tread with strenght blocks, excellent tractive response and great water drainage.

## TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Lenght	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
10	250	9 7/8	17	22/32	4,31	9,50	2,90	14,05	30,97	315/80R22.5	E	3.260	10,695
10.5	260	10 2/8	17	22/32	4,48	9,88	3,01	14,34	31,61	295/80R22.5	M	3.200	10,498
10.5	260	10 2/8	17	22/32	4,48	9,88	3,01	14,62	32,23	315/80R22.5	E	3.260	10,695

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET