

SC 867

Piso Pavimentado
Eje Motriz
Media y Larga Distancia



CARACTERÍSTICAS

Banda con alto poder de tracción. Excelente desempeño kilométrico.

DATOS TÉCNICOS

N#	Ancho		Profundidad		Peso/m/Lbs./Pies			Peso/unit/Lbs.		Neumático recomendado	Tamaño	Largo	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	205	8 2/8	18	23/32	4	8,82	2,69	12,52	27,60	275/80R22.5	P	3.130	10,269
8	205	8 2/8	18	23/32	4	8,82	2,69	12,90	28,44	295/80R22.5	M	3.220	10,564
8	205	8 2/8	18	23/32	4	8,82	2,69	13,25	29,21	12R22.5 11R24.5	E	3.310	10,860
8.5	215	8 5/8	18	23/32	4,20	9,26	2,82	13,10	28,88	275/80R22.5	P	3.120	10,236
8.5	215	8 5/8	18	23/32	4,20	9,26	2,82	13,47	29,70	295/80R22.5	M	3.210	10,531
8.5	215	8 5/8	18	23/32	4,20	9,26	2,82	13,87	30,58	12R22.5 11R24.5	E	3.300	10,827
10	220	9 7/8	18	23/32	4,76	10,49	3,20	15,03	33,14	295/80R22.5	M	3.160	10,367
10	220	9 7/8	18	23/32	4,76	10,49	3,20	15,80	34,83	12R22.5 11R24.5	E	3.320	10,892
9	225	9	18	23/32	4,40	9,70	2,96	13,68	30,16	275/80R22.5	P	3.110	10,203
9	225	9	18	23/32	4,40	9,70	2,96	14,10	31,09	295/80R22.5	M	3.200	10,499
9	225	9	18	23/32	4,40	9,70	2,96	14,52	32,01	12R22.5 11R24.5	E	3.300	10,827
9.5	235	9 4/8	18	23/32	4,59	10,12	3,08	14,22	31,35	275/80R22.5	P	3.100	10,171
9.5	235	9 4/8	18	23/32	4,59	10,12	3,08	14,70	32,41	295/80R22.5	M	3.200	10,499
9.5	235	9 4/8	18	23/32	4,59	10,12	3,08	15,15	33,40	12R22.5 11R24.5	E	3.300	10,827
9.5	240	9 4/8	18	23/32	4,59	10,08	3,07	14,20	31,31	275/80R22.5	P	3.110	10,203
9.5	240	9 4/8	18	23/32	4,57	10,08	3,07	14,44	31,83	295/80R22.5	M	3.160	10,367
9.5	240	9 4/8	18	23/32	4,57	10,08	3,07	15,12	33,33	12R22.5 315/80R22.5 11R24.5	E	3.310	10,860
10.5	260	10 2/8	18	23/32	4,95	10,91	3,32	15,62	34,44	295/80R22.5	M	3.160	10,367
10.5	260	10 2/8	18	23/32	4,95	10,91	3,32	16,42	36,20	315/80R22.5	E	3.320	10,892

BANDAS PRECURADAS - SILVERCAP



WWW.SILVERCAP.NET