

SC 867

Recommended Application:

Highway

Optional Application:

Regional

Drive Axle

Medium and Long Distances



CHARACTERISTICS

Pre cured tread rubber high power traction. Excellent performed miles.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	205	8 2/8	18	23/32	4	8.82	2.69	12.52	27.60	275/80R22.5	P	3.130	10,269
8	205	8 2/8	18	23/32	4	8.82	2.69	12.90	28.44	295/80R22.5	M	3.220	10,564
8	205	8 2/8	18	23/32	4	8.82	2.69	13.25	29.21	12R22.5 11R24.5	E	3.310	10,860
8.5	215	8 5/8	18	23/32	4.20	9.26	2.82	13.10	28.88	275/80R22.5	P	3.120	10,236
8.5	215	8 5/8	18	23/32	4.20	9.26	2.82	13.47	29.70	295/80R22.5	M	3.210	10,531
8.5	215	8 5/8	18	23/32	4.20	9.26	2.82	13.87	30.58	12R22.5 11R24.5	E	3.300	10,827
10	220	9 7/8	18	23/32	4.76	10.49	3.20	15.03	33.14	295/80R22.5	M	3.160	10,367
10	220	9 7/8	18	23/32	4.76	10.49	3.20	15.80	34.83	12R22.5 11R24.5	E	3.320	10,892
9	225	9	18	23/32	4.40	9.70	2.96	13.68	30.16	275/80R22.5	P	3.110	10,203
9	225	9	18	23/32	4.40	9.70	2.96	14.10	31.09	295/80R22.5	M	3.200	10,499
9	225	9	18	23/32	4.40	9.70	2.96	14.52	32.01	12R22.5 11R24.5	E	3.300	10,827
9.5	235	9 4/8	18	23/32	4.59	10.12	3.08	14.22	31.35	275/80R22.5	P	3.100	10,171
9.5	235	9 4/8	18	23/32	4.59	10.12	3.08	14.70	32.41	295/80R22.5	M	3.200	10,499
9.5	235	9 4/8	18	23/32	4.59	10.12	3.08	15.15	33.40	12R22.5 11R24.5	E	3.300	10,827
9.5	240	9 4/8	18	23/32	4.59	10.08	3.07	14.20	31.31	275/80R22.5	P	3.110	10,203
9.5	240	9 4/8	18	23/32	4.57	10.08	3.07	14.44	31.83	295/80R22.5	M	3.160	10,367
9.5	240	9 4/8	18	23/32	4.57	10.08	3.07	15.12	33.33	12R22.5 315/80R22.5 11R24.5	E	3.310	10,860
10.5	260	10 2/8	18	23/32	4.95	10.91	3.32	15.62	34.44	295/80R22.5	M	3.160	10,367
10.5	260	10 2/8	18	23/32	4.95	10.91	3.32	16.42	36.20	315/80R22.5	E	3.320	10,892

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET