

# SC 881

Recommended Application:  
Mix Application

Optional Application:  
Off the Road

Drive Axle  
Short Distances



## CHARACTERISTICS

Tread rubber patten application using in rigorous conditions of use, strong blocks offering high traction capability.

## TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	205	8 2/8	20.5	26/32	4,55	10,03	3,06	14,08	31,04	9.00R20	P	3.090	10,138
8	205	8 2/8	20.5	26/32	4,55	10,03	3,06	14,60	32,19	10.00R20	M	3.210	10,537
8	205	8 2/8	20.5	26/32	4,55	10,03	3,06	15,17	33,44	12R22.5   11R24.5	E	3.330	10,925
8.5	220	8 5/8	20.5	26/32	4,84	10,67	3,25	15,25	33,62	295/80R22.5   11R22.5	M	3.150	10,335
8.5	220	8 5/8	20.5	26/32	4,83	10,65	3,25	15,60	34,39	295/80R22.5   11R24.5	ME	3.230	10,597
8.5	220	8 5/8	20.5	26/32	4,83	10,65	3,24	15,93	35,12	12R22.5   11R24.5	E	3.300	10,827
9	230	9	20.5	26/32	5,05	11,13	3,40	15,92	35,10	295/80R22.5   11R22.5	M	3.150	10,335
9	230	9	20.5	26/32	5,05	11,13	3,39	16,30	35,94	295/80R22.5   11R24.5	ME	3.230	10,597
9	230	9	20.5	26/32	5,05	11,13	3,40	16,68	36,77	12R22.5   11R24.5	E	3.300	10,827
9.5	240	9 4/8	20.5	26/32	5,28	11,64	3,55	16,62	36,64	295/80R22.5	M	3.150	10,335
9.5	240	9 4/8	20.5	26/32	5,27	11,62	3,54	17,02	37,52	295/80R22.5   11R24.5	ME	3.230	10,597
9.5	240	9 4/8	20.5	26/32	5,27	11,62	3,54	17,44	38,45	12R22.5   315/80R22.5   11R24.5	E	3.310	10,860
10	250	9 7/8	20.5	26/32	5,49	12,10	3,69	17,30	38,14	295/80R22.5	M	3.150	10,335
10	250	9 7/8	20.5	26/32	5,49	12,10	3,69	17,75	39,13	295/80R22.5   11R24.5	ME	3.230	10,597
10	250	9 7/8	20.5	26/32	5,49	12,10	3,69	18,21	40,15	315/80R22.5	E	3.320	10,892

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET