

# SC 908

Recommended Application:

Highway

Optional Application:

Regional

Trailer Axle

Short and Medium Distances



## CHARACTERISTICS

Tread for diagonal tires excellent performance, developed to avoid cracks in the grooves.

## TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
4.5	135	5 4/8	10	13/32	1,70	3,75	1,14	5,86	12,92	7.00 X 16   7.50 X 16	G	3.450	11,318
5	150	5 7/8	10	13/32	1,86	4,10	1,25	4,42	9,74	7.00 X 16	MICRO	2.380	7,808
5.5	160	6 2/8	10	13/32	1,98	4,37	1,36	4,90	10,80	7.00 X 16   7.50 X 16	MICRO	2.420	7,939
6.5	180	7 1/8	12	15/32	2,58	5,69	1,73	7,84	17,28	9.00X20	P	3.050	10,007
6.5	180	7 1/8	12	15/32	2,58	5,69	1,73	8,14	17,95	9.00X20	M	3.170	10,400
7	190	7 4/8	12	15/32	2,76	6,08	1,85	8,32	18,34	9.00X20	P	3.020	9,908
7.5	200	7 7/8	12	15/32	2,90	6,39	1,95	8,81	19,42	9.00X20	P	3.040	9,973
7.5	200	7 7/8	12	15/32	2,90	6,39	1,95	9,01	19,86	10.00X20	M	3.110	10,203
8	210	8 2/8	12	15/32	3,05	6,72	2,05	9,50	20,94	10.00X20	M	3.110	10,203
8.5	215	8 5/8	12	15/32	3,13	6,90	2,10	9,99	22,02	10.00X22	M	3.200	11,499
8.5	215	8 5/8	12	15/32	3,12	6,88	2,09	10,66	23,50	11.00X22	G	3.420	11,22

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET