

SC 960

Recommended Application:
Mix Application

Optional Application:
Off the Road

Drive Axle
Short and Medium Distances



CHARACTERISTICS

Tread for bias tires with high traction power and resistant to cuts, chip and chunk.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
5	150	5 7/8	12	15/32	2,10	4,63	1,41	5,10	11,24	7.00 X 16	MICRO	2,430	7,972
5.5	160	6 2/8	12	15/32	2,26	4,98	1,52	5,44	11,99	7.00 X 16 7.50 X 16	MICRO	2,410	7,906
6.5	180	7 1/8	15	19/32	3,02	6,66	2,03	7,33	16,16	215/75R17.5	MICRO	2,430	7,972
7	190	7 4/8	15	19/32	3,19	7,03	2,14	7,90	17,42	215/75R17.5	MICRO	2,480	8,136
7	190	7 4/8	15	19/32	3,19	7,03	2,14	9,79	21,58	9.00X20	P	3,070	10,072
7	190	7 4/8	15	19/32	3,19	7,03	2,14	10,17	22,42	10.00X20	M	3,190	10,465
7.5	200	7 7/8	15	19/32	3,39	7,47	2,28	10,70	23,59	10.00X20	M	3,160	10,367
8	210	8 2/8	15	19/32	3,54	7,80	2,37	11,20	24,69	10.00X20	M	3,170	10,4

PRECURED TREADS - SILVERCAP



WWW.SILVERCAP.NET